



WK-9AL HYDRAULIC PUNCH DRIVER with new SPEED PUNCH System

"No Thread" Punch design, effortless punching with quickest speed and most efficiency

- with high strength aluminum alloy body, easy to handle
- compact body, huge power-two stage hydraulic system to deliver fast feed and power stroke
- 360° rotatable working head, widely used in different applications. the working head inlay the spacer to protect the aluminum head

Technical data	
Rated pressure:	86kN
Stroke:	25mm
Max round punch size:	61.5 mm dia In the 3.5mm mild steel
Temperature:	- 20°C-50°C
Weight of box:	355X102X123mm
Accessories:	
Round Knockout Punches:	22.5mm,28.3mm,34.6mm,43.2mm,49.6mm,61.5mm
Speed lock:	1pc
Speed small draw stud:	1pc
Speed middle draw stud:	1pc
Sealing kit:	1set
Plastic box:	1рс



Note: Due to the different material and process of the iron plate, it is impossible to define the accurate hole diameter and plate thickness. The actual test data shall prevail.







TPA-8

- 360° rotatable head
- with high strength aluminum alloy body, easy to handle

Technical data	
Punching range:	In the 3.5mm mild steel
Punching force:	69kN
Stroke:	21mm
Accessories:	
Round Knockout Punches Type D:	22.5,28.3,34.6,43.2,49.6,61.5mm
7/16"×3/4" Draw Stud:	1pc
3/4"×3/4" Draw Stud:	1pc
Spacer:	1pc
Sealing kit:	1set

WK-8

- For easy operation and comfort the operator, the tool head can be fully rotated through 360°
- It gives clean perforation through 3.5mm thick mild steel with a ϕ 61.5mm max hole.

Technical data	
Punching range:	In the 3.5mm mild steel
Punching force:	70kN
Stroke:	25mm
Accessories:	
Round Knockout Punches Type D:	22.5,28.3,34.6,43.2,49.6,61.5mm
7/16"×3/4" Draw Stud:	1pc
3/4"×3/4" Draw Stud:	1pc
Spacer:	1pc
Sealing kit:	1set
Plastic box:	1pc

WK-8AL

- 180°*360° rotatable head, right angle driver head for maximum flexibility in confined working areas with high strength aluminum alloy body, easy to handle
- Allow unlimited driver orientation to simplify access to work area
- Develops 7tons of hydraulic force for easy punching

Technical data	
Punching force:	70kN
Stroke:	26mm
Accessories:	
Round Knockout Punches Type D:	22.5,28.3,34.6,43.2,49.6,61.5mm
7/16"×3/4" Draw Stud:	1pc
3/4"×3/4" Draw Stud:	1pc
Spacer:	1pc
Sealing kit:	1set