







WK-12AL

SYK-8B

up to 3.5mm

punch&die

With hand pump, hose and cylinder

Suitable for mild steel, plastic and aluminum plate

• We can special make for round, square or rectangle

- 180°*360° rotatable head, right angle driver head for maximum flexibility in confined working areas
- with high strength aluminum alloy body, easy to handle
- Allow unlimited driver orientation to simplify access to work area
- Develops 12tons of hydraulic force for easy punching, even in 3.5mm mild steel.

PATTENT NO.: US8.667.790132

Technical data	
Punching range: φ22	.5-φ61.5mm in the 3.5mm Mild Steel
Punching force:	120kN
Stroke:	29mm
Accessories:	
Round Knockout Punches Type D:	22.5,28.3,34.6,43.2,49.6,61.5mm
7/16"×3/4" Draw Stud:	1pc
3/4"×3/4" Draw Stud:	1pc
Spacer:	1pc
Sealing kit:	1set

TP-8C

With high strength of steel body, durable and reliable Suitable for mild steel, plastic and aluminum plate up to 3.5mm

Technical data	
Punching range:	In the 3.5mm mild steel
Punching force:	66kN
Stroke:	22mm
Accessories:	
Round Knockout Punches Type D:	22.5,28.3,34.6,43.2,49.6,61.5mm
7/16"×3/4" Draw Stud:	1pc
3/4"×3/4" Draw Stud:	1pc
Spacer:	1pc
Sealing kit:	1set



SYK-15

- with hand pump, hose and cylinder
- Suitable for mild steel, plastic and aluminum plate up to 3.5mm
- We can special make for round, square or rectangle punch&die

Technical data		
Punching range: φ22.5- φ61.	5mm in the 3.5mm mild steel	
Punching force:	150kN	
Accessories:		
Round Knockout Punches Type D: 22	.5, 28.3, 34.6, 43.2, 49.6, 61.5mm	
Square Knockout Punches :	32x32mm	
7/16"×3/4" Draw Stud:	1pc	
3/4"×3/4" Draw Stud:	1pc	
Spacer:	1pc	
Sealing kit:	1set	





- Aluminum head provides strength with minimum weight, reducing operator fatigue Self-stripping design eliminates punch hang-ups.
- Automatically centers holes on standard studs.



Technical data	
Punching range: φ22.5-	- φ61.5mm in the 3.5mm mild steel
Punching force:	100kN
Accessories:	
Round Knockout Punches Type D:	22.5,28.3,34.6,43.2,49.6,61.5mm
7/16"×3/4" Draw Stud:	1pc
3/4"×3/4" Draw Stud:	1pc
Spacer:	1pc
Sealing kit:	1set

- Punch up through 1.0 mm mild steel in one stroke.

Technical data In the 1.0mm mild steel Punching capacity: φ22.2mm and φ34.1mm Round punch die: 45mm Stroke: 48mm Depth of throat:

HCC-76

- Punch up through 1.0 mm mild steel in one stroke.
- Aluminum head provides strength with minimum weight, reducing operator fatigue. Self-stripping design eliminates punch hang-ups.
- Automatically centers holes on standard studs.

Technical data	
Rated output:	15kN
Rated pressure:	32Мра
Punching range:	Max.Φ34.1mm on 1.5mm below soft steel plate
N.Weight:	approx.5.2kg
Stroke:	45mm
Throat depth:	51.2 - 76.2mm
Package:	Plastic box