

EB-1550 EB-32100 Battery Powered Press Tool New Technology Brushless Motor

- 3-6S to finish one cycle
- Automatic retraction when press is completed
- Two stage hydraulic system
- An ergonomic design and optimized position of center of gravity to provide increased feel and usability
- Micro computer control system



Bluetooth And Pressure Sensor

Thanks to new implemented Bluetooth technology, device-related data can be requested via the ZUPPER APP. The ZUPPER EB Series include BLUETOOTH asbasic configuration, you can choose pressure sensor at optional.

ZUPPER Check-APP

- Data transfer between press tool and APP
- See the location of where your ZUPPER Link enabled tool was last seen.
- Check the pressure by pressure sensor to differentiate the pressure normal or not.
- APP shows the pressure data counter to check and analyze the pressure easily.



Technical Data	EB-1550	EB-32100	
Capacity:	12-54mm for stainless steel pipe	12-54mm for stainless steel pipe	
	12-108mm[1/2"-4"] for PEX,Multi-layer composite and copper pipe	12-108mm(1/2"-4") for PEX,Multi-layer composite and copper pipe	
Output:	32kN	32kN	
Stroke:	40mm	40/60/100mm(adjustable)	
Cycle time:	3-6s(depands on diameter of pipe)	3-6s(depands on diameter of pipe)	
Oil capacity:	115ml	250ml	
Pressing cycles/charge	360cycles(DN20 stainless steel)	360cycles(DN20 stainless steel)	
Battery:	18V Li-ion 4.0Ah	18V Li-ion 4.0Ah	
Charger:	AC 100V-240V 50-60Hz	AC 100V-240V 50-60Hz	
Charging time:	Approx.80mins	Approx.80mins	
Service Interval:	10000cycles	10000cycles	
Weight:	3.8kgs(tool with battery)		
	6.0kgs(tool with battery and jaw)		
Tool Size:	400x318x86mm	525x318x86mm	

Accessories				
	EB-1550	Weight(kgs)	EB-32100	Weight(kgs)
Accessories:	Battery Press Tool Kit without jaws:	9.0	Battery Press Tool Kit without jaws:	
	18V Li-ion 4.0Ah	0.6	18V Li-ion 4.0Ah	0.6
Accessories:	Charger	0.5	Charger	0.5
	Plastic case	4.1	Plastic case	4.1